



# Product Profile

<b>A1. Model No.:</b>		<b>A2. Product Name:</b>	
FHD668M		IP CAMERA	
<b>B1. Product Keywords:</b>			
1) 1080P 2) Support ONVIF/RTSP 3) IP69K 4) Diagonal Viewing angle: 130° 5) Night vision distance: 10m 6) Anti-vibration: ISO 16750-3 ( Max. 5.9G)			
<b>B2. Product Features:</b>			
1) Night vision distance: 10m 2) Anti-vibration: ISO 16750-3 ( Max. 5.9G)			
<b>B3. Key Specifications:</b>			
Image Device	1/2.9" CMOS		
Frame Rate	2~30 fps		
Effective Pixels	1920(H) x 1080(V)		
Pixel Size	2.8 μm x 2.8μm		
Main Stream Resolution	D1/720P/960P/1080P		
Sub Stream Resolution	CIF/D1		
Audio Format	G.711A/G.711U/LPCM		
AGC	Auto		
Dynamic rang	81dB		
White Balance	Auto		
Electronic Shutter	1/25 (1/30) ~ 1/50,000 Seconds		
BLC	Auto		
Operating Temperature	-20°C ~ 70°C, RH 95% MAX.		
Storage Temperature	-30°C ~ 80°C, RH 95% MAX		
<b>Power Supply (POE)</b>	<b>IEEE 802.3af POE</b>		
<b>Latency</b>	<b>200ms, subject to change with different terminal</b>		
<b>Compression</b>	<b>H.264/H.265</b>		
<b>C1. Accessories:</b>			
1- Manual	1-Network Cable		
1- Screwdriver			
<b>D1. Packing:</b>			
Weight Of Unit Product:		Weight Of Export Carton:	
Dimension Of Giftbox:	12.7*10.2*9.1 (CM)	Dimension Of Export Carton:	40.5*32.5*21 (CM)
20"/40"/40"HQ Qty:		Qty Per Carton:	
<b>E1. Payment Term:</b>		<b>F1. Warranty Terms:</b>	
T/T		12 months of warranty	
<b>G1. Certificates:</b>			
	Sample:	Lead time:	7-14 days
<b>I1. Remarks:</b>			